MIC® Tight-Buffered Cable, Plenum

2 F, 62.5 µm multimode (OM1)

CORNING

Corning Cable Systems MIC® Plenum Cables are designed for use in plenum, riser and general purpose environments for intrabuilding backbone and horizontal installations. These multi-fiber cables use 900 µm TBII® Buffered Fibers to allow easy, consistent stripping and to facilitate termination. The fibers are surrounded by dielectric strength members and protected by a flame-retardant outer jacket. The all-dielectric cable construction requires no grounding or bonding. MIC Plenum cables are ideal for routing inside buildings, within plenum areas and riser shafts, to the telecommunications rooms and workstations. The MIC Plenum Cables meet the application requirements of the National Electrical Code® (NEC®) Article 770 and are OFNP and FT-6 listed.



Part Number: 002K88-31130-29



Cross Section of Part Number: 002K88-31130-29

Features and Benefits

900 µm TBII® Buffered Fibers
Easy, consistent stripping

All-dielectric construction
Requires no grounding or bonding

Flame-retardant jacket
Rugged and durable

Standards

Approval and Listings	National Electrical Code® (NEC®) OFNP, CSA FT-6, ICEA S-83-596
Flame Resistance	

RoHS COMPLIANT

CORNING

MIC® Tight-Buffered Cable, Plenum

2 F, 62.5 µm multimode (OM1)

CORNING

Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Distribution
Flame Rating	Plenum (OFNP)
Fiber Category	62.5 µm MM (OM1)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Design	
Central element	Yarn
Fiber Count	2
Tight buffer color	Blue, Orange
Tensile strengths elements / armoring	Dielectric strength members
Outer jacket material	Flame-retardant
Outer jacket color	Orange

Mechanical Characteristics Cable	
Max. Tensile Strengths, Short-Term	440 N (100 lbf)
Max. Tensile Strengths, Long-Term	132 N (30 lbf)
Nominal Outer Diameter	5.0 mm (0.2 in)
Weight	21.0 kg/km (15.0 lb/1000 ft)
Min. Bend Radius Installation	75.0 mm (3.0 in)
Min. Bend Radius Operation	25.0 mm (1.0 in)

CORNING

MIC® Tight-Buffered Cable, Plenum

2 F, 62.5 µm multimode (OM1)

CORNING

Fiber Specifications

Optical Characteristics (cabled)	
Fiber Core Diameter	62.5 µm
Fiber Type	Multimode
Fiber Category	OM1
Fiber Code	K
Performance Option Code	30
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.4 dB/km / 1.0 dB/km
Min. Overfilled Launch (OFL) Bandwidth	200 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	220 MHz*km / -
Serial 1 Gigabit Ethernet	300 m / 550 m
Serial 10 Gigabit Ethernet	33 m / -

Notes: 1) Improved attenuation and bandwidth options available
2) Bend-insensitive single-mode fibers available on request
3) Contact a Corning Cable Systems Customer Service Representative for additional information

Ordering Information

Order Number	002K88-31130-29
Product description	MIC® Tight-Buffered Cable, Plenum, 2 F, 62.5 µm multimode (OM1)

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems
A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.
Corning Cable Systems is ISO 9001 certified. © 2010 Corning Cable Systems. All rights reserved.

CORNING